

RODE PERFORMANCE

	Stretch %	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%
10-FT X 1.38 RODE	10-FT	11-FT	12-FT	13-FT	14-FT	15-FT	16-FT	17-FT	18-FT	19-FT	20-FT
AVERAGE LOAD	0	65	166	244	307	359	397	436	465	494	533
5-FT X 1.38 RODE	5-FT	5.5-FT	6-FT	6.5-FT	7-FT	7.5-FT	8-FT	8.5-FT	9-FT	9.5-FT	10-FT
AVERAGE LOAD	0	90	191.5	268.5	331	382.5	420	459.5	488	517	556.5
3-FT X 1.38 RODE	3-FT	3.3-FT	3.6-FT	3.9-FT	4.2-FT	4.5-FT	4.8-FT	5.1-FT	5.4-FT	5.7-FT	6-FT
AVERAGE LOAD	0	90	191.5	268.5	331	382.5	420	459.5	488	517	556.5
<u>Load on 100% elongation</u>											
10-FT X 1.38 average load 4.6-lbs/inch.											
5-FT X 1.38 average load 9.2-lbs/inch.											
3-FT X 1.38 average load 15-lbs/inch.											



PPR Waterworks Sdn Bhd (371605-U) No. 9, Jalan Tambur 33/198, Shah Alam Tech. Park, 40400 Shah Alam, Selangor, Malaysia.
 Tel: 603-51247392 Fax: 603-51231212 Email: superfloats@yahoo.com Website: www.superfloats.com

Superfloats EMS-C
(Extendable Mooring System)